



## Perma-tec Cable Support

The Perma-tec Cable Strap System is a user-friendly product designed to provide ease and flexibility in fastening cables to Permaglass Pump Column.

This system includes weather-resistant acetal cable straps and marine grade locking devices.

### **Advantages of the Perma-tec System Include:**

- 10 years + proven bore service.
- No sharp edges.
- High tensile strength after fastening.

### **Specifications . . . . .**

- Minimum Tensile Strength: 1,211N minimum.
- Outdoor Life: Designed to last a minimum of 20 years.
- Continuous Load: 9.07 kg
- Continuous Use Temperature: -65 C to 90 C
- Colour: Black.
- Strap and Body: Weatherable acetal; offers superior resistance to sunlight, moisture, and salt environments.
- Locking Device: Marine-grade corrosion-resistant silicon copper alloy.

Distributed By:  
Advanced Pump Technologies  
Ph: 08 6143 1000  
E: [info@advancedpumps.com.au](mailto:info@advancedpumps.com.au)  
W: [www.advancedpumps.com.au](http://www.advancedpumps.com.au)



## Perma-tape Cable Support

Perma-tape is a heavy duty PVC pipe protection tape coated with an anti-corrosive and aggressive adhesive. It is designed for above ground and underground applications making it suitable for use in bore holes.

Perma-tape is user-friendly in its installation and is designed to provide ease and flexibility in fastening cables to Permaglas Pump Column.

The recommended installation is for Perma-tape to be wrapped around the bell ends to prevent silt build up in the joint. Perma-tape should also be wrapped around the electrical cable at 2m intervals for cables up to 1.7kg/m for support. Perma-tape should also be wrapped around the stainless steel locking wire to prevent damage to the cable and bore casing. For cables over 1.7kg/m, refer to Perma-tec Cable strap.

### **Advantages of the Perma-tape System Include:**

- 5 years of proven bore service.
- No sharp edges.
- High tensile strength after fastening.

### **Specifications . . . . .**

- Dimensions: 72mm wide x 0.25mm thick
- Roll length: 33m
- Breaking load: 44N/cm
- Elongation: 220%
- Continuous Use Temperature: -5 C to 80 C
- Colour: Black

Distributed By: Advanced Pump Technologies Ph: 08 6143 1000 E: <a href="mailto:info@advancedpumps.com.au">info@advancedpumps.com.au</a> W: <a href="http://www.advancedpumps.com.au">www.advancedpumps.com.au</a>
---